

DG 14K LOW-PROFILE DUMP

STANDARD FEATURES

THESE ARE THE DEFAULT FEATURES THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

Inside Bed Width: 83"	Deck Height: 28"	Cargo Capacity: 6 yd³	Dump Angle: 40°
Lengths: 14'	Couplers: Bumper Pull & Pintle	Axles: Tandem (2 x 7,000 lb.)	Choose the optional 6' 6" Slide-In Channel Ramps for easy equipment loading.
GVWR: 14,000 lbs.	Load Capacity: 10,500 lbs.	Dump Sides Height: 20"	



With its sturdy construction and reliable performance, the Seamless I-Beam creates a more robust and dependable frame, ensuring that your dump trailer can handle even the most demanding jobs.

SEAMLESS I-BEAM FRAME DESIGN



Our UniWall Steel Technology uses form-rolled steel to add structural integrity, reduce corrosion-vulnerable seams, and lower the trailer weight to increase load capacity.

UNIWALL STEEL TECHNOLOGY



The Ramp Ready feature equips your dump trailer with rear ramp pockets and doors (ramps sold separately), making it easy to load and unload heavy equipment quickly.

RAMP READY!



The Scissor-Lift Hydraulic System provides efficient lifting capabilities, a stable lifting platform and power-up/power-down functionality for quick dump cycles.

SCISSOR LIFT WITH POWERFUL CYLINDER

PJ TRAILERS

Visit pjtrailers.com for a complete list of trailer options.