












DX 83" PRO-LIFT DUMP

STANDARD CONFIGURATION SPECS

THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

 Inside Bed Width: 83"	 Deck Height: 29"	 Cargo Capacity: 7.2 yd³ (up to 16.4 yd³)	 Dump Angle: 40°
 Length: 12', 14', 16'	 Couplers: Bumper Pull, Gooseneck, & Pintle	 Axles: Tandem (2 x 8,000 lbs.)	 Choose the optional Hydraulic Jacks for effortless press-button control and ease.
 GVWR: 16,000 lbs.	 Load Capacity: 12,500 lbs.	 Dump Sides Height: 24" (36" & 48" Optional)	



Our oil bath lubrication system and Valcrum Oil Caps simplify axle maintenance by keeping them properly lubricated and allowing for easy oil level checks without worrying about broken plastic caps.

OIL BATH AXLES WITH VALCRUM OIL CAPS



Our UniWall Steel Technology uses form-rolled steel to add structural integrity, reduce corrosion-vulnerable seams, and lower the trailer weight to increase load capacity.

UNI-WALL STEEL TECHNOLOGY



The Scissor-Lift Hydraulic System provides efficient lifting capabilities, a stable lifting platform and power-up/power-down functionality for quick dump cycles.

SCISSOR-LIFT WITH POWERFUL CYLINDER



The Demco EZ Latch Coupler system makes hookup a breeze. With its easy and secure design, you won't have to fumble with complicated locking mechanisms or struggle to connect your trailer to your vehicle. Just drop and go!

DEMCO EZ LATCH COUPLER

PJ TRAILERS

Visit pjtrailers.com for a complete list of trailer options.