STANDARD CONFIGURATION SPECS

THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

TH 83" HYDRAUILC QUICK TILT

w Deck Width: 83"	■ Deck Height: 24"	Axles: Tandem (2 x 5,200 lb.)	Choose the optional Blackwood Pro decking for added durability and grip when wet.
Length: 18' - 22'	Couplers: Bumper Pull & Pintle	ी Load Capacity: 7,300 - 7,600 lbs.	
GVWR: 10,000 lbs.	Weight: 2,400 - 2,700 lbs.	Tilt Angle: 10°	





Our front Ram Hydraulic powered system gives you additional stability and control over the precise up and down movement of the bed for additional ease of use and loadinglunloading flexibility.

HYDRAULIC POWERED TILT DECK



Simplify broke maintenance with our Forward Self-Adjusting Brokes, engineered to self-adjust for optimal broking performance. This innovative system reduces downtime and ensures consistent stopping power.

FORWARD SELF-ADJUSTING BRAKES



Benefit from enhanced cargo securement with our standard full-length Rubrail and stake pockests. In addition to the built-in stake pockets, the Rubrail provides extra attachment points for securing gour load. Dustomize your trailer further by adding optional D-rings.

CARGO CONTROL STANDARD



