THESE ARE THE DEFAULT FEATURES THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

D3 72" TANDEM AXLE DUMP

w Inside Bed Width: 72"	E Deck Height: 28"	according Cargo Capacity: 3.7 - 10.7 yd³	Dump Angle: 40°
Lengths: 10', 12'	Couplers: Bumper Pull & Pintle	Axles: Tandem (2 x 5,200 lb.)	Choose the optional Gravity-Down unit to reduce battery consumption.
OVWR: 9,900 lbs.	Load Capacity: 6,970 - 7,240 lbs	☆! Dump Side Height: 20" (48" optional)	





The Self-Contained Hydraulic Unit provides reliable power for your dump trailer, while the Front-Locking Toolbox offers secure storage for your equipment.

SELF-CONTAINED HYDRAULIC UNIT & FRONT-LOCKING TOOLBOX



Our UniWall Steel Technology uses formrolled steel to add structural integrity, reduce corrosion-vulnerable seams, and lower the trailer weight to increase load capacity.

UNIWALL STEEL TECHNOLOGY



Enhance your trailer's versatility with our optional 2-Way Gate System, which combines the functionality of a barn door and spreader. This feature allows for maximum load dumping flexibility.

2-WAY GATE SYSTEM (OPTIONAL)



The Demco EZ Latch Coupler system makes hookup a breeze. You'll never have to fumble with complicated locking mechanisms or struggle to connect your trailer to your vehicle.

DEMCO EZ LATCH COUPLER

