## **STANDARD CONFIGURATION SPECS**

THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

## DM 83" PRO-LIFT DUMP

Inside Bed Width: 83"	Deck Height: 28" (24" Optional)	argo Capacity: 9.2 yd³ (up to 16.4 yd³)	Dump Angle: 40°
Length: <b>14', 16'</b>	Couplers: Bumper Pull, Gooseneck, & Pintle	Axles: <b>Tandem (2 x 7,000 lb.)</b>	+ Choose the optional 7,000 lb. Electric Drop Axles for an ultra-low 24" bed height.
<b>GVWR: 14,000 - 15,680 lbs.</b>	Load Capacity: <b>8,820 - 9,970 lbs.</b>	ी Dump Sides Height: 36" (48" Optional)	





With its sturdy construction and reliable performance, the Seamless I-Beam creates a more robust and dependable frame, ensuring that your dump trailer can handle even the most demanding jobs.

**SEAMLESS I-BEAM FRAME DESIGN** 



The Scissor-Lift Hydraulic System provides efficient lifting capabilities, a stable lifting platform and power-up/power-down functionality for quick dump cycles.

SCISSOR LIFT WITH POWERFUL CYLINDER



This model comes standard with 6' 6' Slide-Ir Channel Ramps to ensure effortless loading and unloading of heavy equipment. The integrated ramp system boosts your trailer's functionality, allowing you to houl anything your job requires.

**EQUIPMENT READY!** 



The above-average 36" Dump Box Walls provide a large volume capacity, allowing you to easily houl and transport various materials, and the sturdy construction provides long-lasting

TALLER 36" SIDES (48" OPTIONAL)

