












DT 83" PRO-LIFT DUMP

STANDARD CONFIGURATION SPECS

THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

 Inside Bed Width: 83"	 Deck Height: 28" (24" Optional)	 Cargo Capacity: 7.2 - 16.4 yd³	 Dump Angle: 40°
 Length: 14', 16'	 Couplers: Bumper Pull, Gooseneck, & Pintle	 Axles: Tandem (2 x 7,000 lb. or 8,000 lb.)	 Choose the optional 7,000 lb. Electric Drop Axles for an ultra-low 24" bed height.
 GVWR: 14,000 - 16,000 lbs.	 Load Capacity: 9,750 - 11,920 lbs.	 Dump Sides Height: 24" (36" & 48" Optional)	



With its sturdy construction and reliable performance, the Seamless I-Beam creates a more robust and dependable frame, ensuring that your dump trailer can handle even the most demanding jobs.

SEAMLESS I-BEAM FRAME DESIGN



Our UniWall Steel Technology uses form-rolled steel to add structural integrity, reduce corrosion-vulnerable seams, and lower the trailer weight to increase load capacity.

UNI-WALL STEEL TECHNOLOGY



Featuring a 3-stage telescopic cylinder mounted on the tongue, you will have a smooth lift experience from start to finish while getting more dump cycles per charged battery.

12-TON TELESCOPIC CYLINDER



Our 3' and 4' high side options are great for hauling bulky loads. When using these options with the included rollup tarp kit, you can safely transport loads to and from job sites.

3' & 4' HIGH SIDES OPTIONS