STANDARD CONFIGURATION SPECS

THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

CD 6" CHANNEL EQUIPMENT

DECK HEIGHT: 22"

DECK WIDTH: 83"

┥┝

..... LENGTH: 18'- 22' **COUPLER: Bumper Pull** LOAD CAPACITY: 11,380-10,980 lbs. 6. o Ibs GVWR: 14,000 lbs. WEIGHT: 2,620-3,020 lbs. Focused feature set to give you a solid value. 5' Fold-Up Ramps With Support Feet 32" Wood-Filled Dovetail Removable Front Bump Rail Treadplate Steel Fenders I 83" Wide Deck 2-5/16" Adjustable Coupler - marine - marine - marine PITRAILERS Constant of 7K Axles with Forward Self-Adjusting Brakes (6) Welded on 6" Channel Stake Pockets Drop-Leg Jack Frame & Tongue (7,000 lb.) ST235/80R16 LR-E (10-PLY) ⊢ Radial Tires Adjustable coupler helps ensure your The 32" wood-filled dovetail with Benefit from 6 standard stake With the removable fender, loading truck hitch and trailer match up to 5' fold-up ramps and support feet pockets that securely hold your wider equipment becomes easier as get the trailer set up for just the right makes it easy to load your cargo vehicle or equipment in place. you gain additional width clearance. trailer deck angle. onto the deck.

RELIABLE CARGO SECUREMENT

AXLES: Tandem (7,000 lbs.)

REMOVABLE FENDERS



ADJUSTABLE COUPLER

VISIT PJTRAILERS.COM FOR A COMPLETE LIST OF TRAILER OPTIONS.

FAST & EFFICIENT LOADING