

## **VOYAGER HYDRAULIC DOVETAIL GOOSENECK**

## STANDARD CONFIGURATION SPECS

THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

DECK WIDTH: 102"	DECK HEIGHT: 33"	CARGO CAPACITY: 14,007 - 21,460 lbs.	RAMP ANGLE: 12 Degrees
<b>LENGTH:</b> 32' - 40'	COUPLERS: Gooseneck	AXLES: Tandem (2 x 10,000 lbs., 12,000 lbs. or 15,000 lbs.)	
<b>&amp;</b> GVWR: 25,000 - 30,000 lbs.	WEIGHT: 8,540 - 10,993 lbs.	TAIL TYPES: 12-12-12 Hydraulic Dovetail	







12' long, 12,000 lb. lifting capacity and 12-degree ramp angle put the LY at the front of the pack for easy loading of heavy equipment.

INDUSTRY-LEADING HYDRAULIC



Rear traction bars on diamond plate steel deck allow for wet and muddy conditions to not slow loading equipment with a variety of wheels or tracks.

**REAR TRACTION** 



With the easy-to-use below-thedeck spare mount, getting the tire down to change a tire is just as easy as your truck.

BELOW DECK SPARE



The engineered neck provides strength and easy hitching with the Demco EZ Latch.

ENGINEERED PROBEAM™ WITH DEMCO EZ LATCH

**IIPJTRAILERS**